

THOMSON

DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Home](#) | [About Delphion](#) | [Privacy Policy](#) | [My Account](#) | [Products](#)
[Search: Quick/Number](#) | [Boolean](#) | [Advanced](#)

The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: Add to Work File: [Create new Wor](#)

 View: [INPADOC](#) | Jump to: [Top](#) | Go to: [Derwent...](#)
[Email](#)

Title: JP10289708A2: NONAQUEOUS ELECTROLYTE SECONDARY BATT
MANUFACTURE OF ELECTRODE PLATES OF THE SAME

Country: JP Japan

Kind: A

Inventor: MURAI TETSUYA;
TSUKAMOTO HISASHI;

Assignee: JAPAN STORAGE BATTERY CO LTD
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1998-10-27 / 1997-04-11

Application Number: JP1997000094026

IPC Code: H01M 4/02; H01M 4/04; H01M 10/40;

Priority Number: 1997-04-11 JP1997000094026

Abstract:


.... PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

.... SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

.... COPYRIGHT: (C)1998,JPO

Family: None

Other Abstract Info: CHEMABS 129(25)333313V CAN129(25)333313V DERABS C99-020193
DERC99-020193



[this for the Gallery...](#)

[Nominate](#)

© 1997-2003 Thomson Delphion | [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)

BEST AVAILABLE COPY

THOMSON		DELPHION		RESEARCH	PRODUCTS	INSIDE DELPHION
Home	About Us	Contact Us	My Account	Products	Search: Quick/Number	Boolean Advanced

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#) Tools: Add to Work File: [Create new Work File](#)

View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent...](#) [Email](#)

Title: JP10289708A2: NONAQUEOUS ELECTROLYTE SECONDARY BATT
MANUFACTURE OF ELECTRODE PLATES OF THE SAME

Country: JP Japan
Kind: A

Inventor: MURAI TETSUYA;
TSUKAMOTO HISASHI;

Assignee: JAPAN STORAGE BATTERY CO LTD
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1998-10-27 / 1997-04-11

Application Number: JP1997000094026

IPC Code: [H01M 4/02](#); [H01M 4/04](#); [H01M 10/40](#);

Priority Number: 1997-04-11 JP1997000094026

Abstract:


PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO

Family: None

Other Abstract Info: CHEMABS 129(25)333313V CAN129(25)333313V DERABS C99-020193
DERC99-020193



[Nominate](#)

[this for the Gallery...](#)



(19)

(11) Publication number: **10**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **09094026**(51) Intl. Cl.: **H01M 4/02 H01M 4/04 H01M**(22) Application date: **11.04.97**

(30) Priority:	(71) Applicant: JAPAN STORAGE BAT LTD
(43) Date of application publication: 27.10.98	(72) Inventor: MURAI TETSUYA TSUKAMOTO HISASHI
(84) Designated contracting states:	(74) Representative:

**(54) NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY
AND MANUFACTURE OF
ELECTRODE PLATES OF
THE SAME**


(57) Abstract:

PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is

produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO



BEST AVAILABLE COPY



(19)

(11) Publication number: **10**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **09094026**(51) Intl. Cl.: **H01M 4/02 H01M 4/04 H01M**(22) Application date: **11.04.97**

(30) Priority: (43) Date of application publication: 27.10.98 (84) Designated contracting states:	(71) Applicant: JAPAN STORAGE BAT LTD (72) Inventor: MURAI TETSUYA TSUKAMOTO HISASHI (74) Representative:
--	---

**(54) NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY
AND MANUFACTURE OF
ELECTRODE PLATES OF
THE SAME**


(57) Abstract:

PROBLEM TO BE SOLVED: To provide a nonaqueous electrolyte secondary battery which can spread lithium on an entire electrode body uniformly as much as possible and enables large quantification, and a manufacturing method of its electrode plates.

SOLUTION: A lithium foil laminated film 50 which holds a metallic lithium foil 52 on a base film 51 is piled on a negative electrode plate 20 and pressurized with passing through between a pair of transcription rolls 53. After pressurization, the base film 51 is peeled off and the negative electrode plate 20, wherein very thin metallic lithium foil 52 is transcribed on the surface of electrode mix 23, is

produced. The negative electrode plate 20 is wound together with a positive electrode plate, placing a separator between them to form an electrode body.

COPYRIGHT: (C)1998,JPO.



BEST AVAILABLE COPY